



Nano SPY T3

Mini Extreme Temperature Data logger
2,4GHz radiofrequency communication



Non contractual photo

Presentation

The Nano SPY T3 measures and records temperature with its external probe. It transmits the data to a nearby LINK module via 2.4 GHz radio frequency communication.

The data are then automatically sent to the JRI secure Cloud for hosting, and will be managed from JRI MySirius web application.

If thresholds are exceeded, alerts are transmitted in real time to react immediately.

Designed to monitor thermo-controlled chambers, the sensor can be fixed thanks to its magnet outside the equipment.

Technical features

	Low T°C Version	High T°C Version
Interface	Status LED and On/Off touch sensitive button	
Measurement range	-200°C to 0°C	0°C to +260°C
Accuracy	±0.2°C from -20°C to 0°C ±0.5°C out of this range	±0.3°C from 0°C to +100°C ±0.5°C out of this range
Communication frequency	2,4 GHz (802.15.4)	
Memory	10 000 data points	
Sensor	External stainless steel PT100 - Ø2,9x25mm	
Operating conditions	-20°C to +50°C	
Resolution	0.01	
Measuring and transmission frequency	Adjustable from 5 sec to 12hrs	
Recording frequency (internal memory)	Adjustable from 5 sec to 24 hrs	
Response time	~ 2mn at 90% of the variation	
Protection	IP65	
Case	Polycarbonate – Food contact	
Power supply	Lithium 3,6v battery - Replaceable	
Battery life	2 to 4 years depending on use	
Dimensions and weight	63 x 42 x 25 mm / ~ 60 g	
Cable lenght	50 cm or 3m	3m
Fixation	Fixing eyelets and integrated magnets	
Supplied with	Battery, red identification ring User manual can be download on www.jri-maxant.com	
Compliance	CE, ROHS, FCC, ETS 300-328, EN 12830	
Standard calibration points	-80°C / +5°C	+20°C / +100°C

Benefits

- **Easy-to-use**
The sensor is ready to use and has operating and alarm lights



- **Excellent measurement accuracy**



Fixing eyelets



Replaceable battery and non disconnectable probe

PART NRS

11693 : Nano SPY T3 3m (High T°C)
11572 : Nano SPY T3 50cm (Low T°C)
11573 : Nano SPY T3 3m (Low T°C)